

texchanges

LaTeX-native track changes

Phuc Nguyen

Version 0.2.2, 14 August 2026

Abstract

Texchanges records additions, removals, replacements, highlights, and comments directly in LaTeX source. The same document can show review markup, proposed final text, or the original text. Registered authors, stable change IDs, and decision statuses support human review and automated editing workflows.

Contents

1	Installation	1
2	Core commands	1
3	Authors, IDs, and decisions	2
4	Document modes	2
5	Reports	2
6	Presentation and localization	3
7	Compatibility with changes	3
8	Resolving source markup	3
9	Resources and license	3

1 Installation

After the package reaches your TeX distribution, install it with the normal package manager and load it with:

```
\usepackage[review]{texchanges}
```

For Overleaf projects whose TeX Live version does not contain Texchanges, upload `texchanges.sty` beside the main document. The project can then use the same package line.

2 Core commands

The native API uses the source order “old, new” for replacements.

```

\txadd{new text}
\txremove{old text}
\txreplace{old text}{new text}
\txhighlight{important text}
\txcomment{Check this claim.}

```

The short aliases `\add`, `\remove`, and `\replace` are installed only when another package has not defined them.

3 Authors, IDs, and decisions

```

\txdefineauthor[name={Phuc Nguyen},color=orange]{phuc}

\txreplace[
  author=phuc,
  id=R12,
  comment={Clarify this claim.},
  status=pending
]{old text}{new text}

```

The optional keys are `author`, `id`, `comment`, and `status`. Status accepts `pending`, `accepted`, or `rejected`. Non-empty change IDs must be unique. A legacy optional label such as `\txadd[Reviewer]{text}` remains available for visual labels without structured author meta-data.

4 Document modes

Mode	Pending	Accepted	Rejected
review	marked change	proposed text	original text
final	proposed text	proposed text	original text
original	original text	original text	original text

Final mode warns when pending changes remain. Change lists and summaries are review artifacts, so `\txlistofchanges` produces no output in final or original mode.

5 Reports

Detailed reports include excerpts, IDs, page numbers, and links when `hyperref` is loaded. Summary reports group counts by author, type, and status. Run LaTeX twice after changes to refresh report data.

```

\txlistofchanges
\txlistofchanges[style=summary]
\txlistofchanges[
  title={Pending reviewer changes},
  show={added,replaced,commented},
  status={pending},
  author={phuc}
]

```

6 Presentation and localization

Presets are `texchanges`, `default`, `underlined`, `bfit`, and `nocolor`. Individual added, deleted, highlighted, comment, and author renderers can be selected through package options or replaced at runtime. English, British English, German, French, Italian, and Vietnamese report labels follow Babel or Polyglossia when their caption hooks are available.

7 Compatibility with changes

Compatibility is opt in because the replacement argument order differs.

```
\usepackage[review,compat=changes]{texchanges}
\definechangesauthor[name={Phuc Nguyen},color=orange]{phuc}
\replaced[id=phuc,changeid=R12]{new text}{old text}
```

The compatibility option provides documented `changes` commands and setter aliases. Its `id` key identifies an author, while `changeid` stores the Texchanges change ID. The `commandname` prefix option accepts `none`, `ifneeded`, or `always`.

8 Resolving source markup

The supplemental standard-library Python tool can update decisions or remove resolved markup permanently.

```
python3 scripts/texchanges_merge.py paper.tex reviewed.tex --accept
python3 scripts/texchanges_merge.py paper.tex final.tex --accept --merge
python3 scripts/texchanges_merge.py paper.tex --reject --id R12 --in-place
```

In-place edits create a backup. The parser handles nested groups and skips comments and common verbatim-like environments. Malformed input fails before the destination is written.

9 Resources and license

Project documentation, examples, releases, and issue reporting are available at <https://phucnht.github.io/texchanges/> and <https://github.com/phucnht/texchanges>.

Texchanges is maintained by Phuc Nguyen. It may be distributed and modified under the LaTeX Project Public License, version 1.3c or later.